

3. CHANNELS

Protective Cover for Wire Routing

Channel ductings are used to provide a protective cover against cement and screed water during wire installation; it also ensures that wire paths and locations are easily located for maintenance.

Risers are used to redirect the wires from underfloor ductings to wall outlets, giving you both the choice and flexibility to install power outlets on the wall.

Three Stars offers Channel Ductings and Risers fabricated from both Pre-Galvanised Steel and uPVC.

DUCT : 2 CHANNEL & 3 CHANNEL

Material : Pre - Galvanised Steel
 Delivery Length : 2.4m
 Duct Height : 28 mm



2 - Channel Duct	Duct Width (mm)	Channels (mm : mm)
CD 7 . 7 - 2	140	70 : 70
CD 12 . 7 - 2	190	120 : 70
CD 15 . 9 - 2	240	150 : 90
3 - Channel Duct	Duct Width (mm)	Channels (mm : mm : mm)
CD 7 . 6 . 6 - 3	190	70 : 60 : 60
CD 12 . 6 . 6 - 3	240	120 : 60 : 60
CD 7,5 . 7,5 . 7,5 - 3	225	75 : 75 : 75
CD 10 . 10 . 10 - 3	300	100 : 100 : 100

RISER : 2 CHANNEL & 3 CHANNEL

Material : Pre - Galvanised Steel



2 - Channel Riser	Duct Width (mm)	Channels (mm : mm)
R 7 . 7 - 2	140	70 : 70
R 12 . 7 - 2	190	120 : 70
R 15 . 9 - 2	240	150 : 90
3 - Channel Riser	Duct Width (mm)	Channels (mm : mm)
R 7 . 6 . 6 - 3	190	70 : 60 : 60
R 12 . 6 . 6 - 3	240	120 : 60 : 60
R 7,5 . 7,5 . 7,5 - 3	225	75 : 75 : 75
R 10 . 10 . 10 - 3	300	100 : 100 : 100

UPVC CHANNEL

Material : uPVC
 Delivery Length : 3.0 m
 Duct Height : 28 mm



PVC Duct	Duct Width (mm)
PCD . 75	75
PCD . 100	100